Pomegranate Noir #TCDL-CFRA-BOWL-NPOM

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 3/23/2018 Revision date: 3/11/2021 Supersedes version of: 7/10/2019 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Product name	:	**Pomegranate Noir** #TCDL-CFRA-BOWL-NPOM
UFI	:	16JP-M1GE-S00D-7YW5
Product code	:	TCDL-CFRA-BOWL-NPOM
Type of product	:	Perfumes, fragrances
Product group	:	Finished Good

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	:	Industrial use
Industrial/Professional use spec	:	For professional use only
Use of the substance/mixture	:	Perfumes, fragrances
Function or use category	:	Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

The Cosy Owl
20-28 Albert Road,
Braintree,
Essex CM7 3JQ
Tel: +44 1376 560 348
enquiries@cosyowl.com – www.cosyowl.com
Company registration number: 07738645

1.4. Emergency telephone number

Emergency number: +44 1376 560 348

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS07 GHS09

Signal word (CLP) : Warning
Contains : Methyl oct-2-ynoate; Hexyl cinnamic aldehyde; Aldehyde C-16; Benzyl benzoate

Hazard statements (CLP) : H302 - Harmful if swallowed.
H317 - May cause an allergic skin reaction.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	(CAS-No.) 120-51-4 (EC-No.) 204-402-9 (EC Index-No.) 607-085-00-9 (REACH-no) 01-2119976371-33	47.7 – 67.7	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Aldehyde C-16	(CAS-No.) 77-83-8 (EC-No.) 201-061-8 (REACH-no) 01-2119967770-28	5 – 10	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Hexamethylindanopyran	(CAS-No.) 1222-05-5 (EC-No.) 214-946-9 (EC Index-No.) 603-212-00-7 (REACH-no) 01-2119488227-29	1.25 – 2.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Verdox	(CAS-No.) 88-41-5 (EC-No.) 201-828-7 (REACH-no) 01-2119970713-33	1.125 – 2.25	Aquatic Chronic 2, H411
Dimethylbenzyl carbinyl butyrate(DMBCB)	(CAS-No.) 10094-34-5 (EC-No.) 233-221-8 (REACH-no) 01-2120742578-44	1 – 2	Skin Irrit. 2, H315 Aquatic Chronic 2, H411
Aldehyde C-14	(CAS-No.) 104-67-6 (EC-No.) 203-225-4 (REACH-no) 01-2119959333-34	0.875 – 1.75	Aquatic Chronic 3, H412
Vanillin	(CAS-No.) 121-33-5 (EC-No.) 204-465-2 (REACH-no) 01-2119516040-60	0.75 – 1.5	Eye Irrit. 2, H319
Citronellyl acetate (mixed Isomers)	(CAS-No.) 150-84-5 (EC-No.) 205-775-0	0.75 – 1.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411
Veltol plus crystals	(CAS-No.) 4940-11-8 (EC-No.) 225-582-5	0.5 – 1	Acute Tox. 4 (Oral), H302
Hexyl cinnamic aldehyde	(CAS-No.) 101-86-0 (EC-No.) 202-983-3 (REACH-no) 01-2119533092-50	0.5 – 1	Skin Sens. 1, H317 Aquatic Chronic 2, H411

Ethyl acetate substance with a Community workplace exposure limit	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46	0.25 – 0.5	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336
Methyl oct-2-ynoate	(CAS-No.) 111-12-6 (EC-No.) 203-836-6	0.25 – 0.5	Aquatic Acute 1, H400 Aquatic Chronic 3, H412 Skin Sens. 1A, H317
Lime oil distilled	(CAS-No.) 8008-26-2 (EC-No.) 290-010-3;616-919-0	0.1 – 0.2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 1, H410
Liffarome	(CAS-No.) 67633-96-9 (EC-No.) 266-797-4	0.1 – 0.2	Skin Sens. 1B, H317

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of water/... If skin irritation or rash occurs: Get immediate medical advice/attention. Get medical advice/attention. Specific treatment (see Wash skin with plenty of water, Call a physician immediately on this label). Wash contaminated clothing before reuse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause an allergic skin reaction.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures	: Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage temperature	: 25 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Store in a closed container.
Packaging materials	: Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	734 mg/m³
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m³
IOEL STEL [ppm]	400 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	734 mg/m³
MAK (OEL TWA) [ppm]	200 ppm
MAK (OEL STEL)	1468 mg/m³
MAK (OEL STEL) [ppm]	400 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	734 mg/m³
GVI (OEL TWA) [2]	200 ppm
KGVI (OEL STEL)	1468 mg/m³
KGVI (OEL STEL) [ppm]	400 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	700 mg/m³
Denmark - Occupational Exposure Limits	
OEL TWA [1]	540 mg/m³
OEL TWA [2]	150 ppm

Ethyl acetate (141-78-6)	
Estonia - Occupational Exposure Limits	
OEL TWA	500 mg/m³
OEL TWA [ppm]	150 ppm
OEL STEL	1100 mg/m³
OEL STEL [ppm]	300 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	730 mg/m³
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	1470 mg/m³
HTP (OEL STEL) [ppm]	400 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	1400 mg/m³
VME (OEL TWA) [ppm]	400 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	730 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Gibraltar - Occupational Exposure Limits	
OEL TWA	200 mg/m³
OEL TWA [ppm]	734 ppm
OEL STEL	400 mg/m³
OEL STEL [ppm]	1468 ppm
Greece - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	734 mg/m³
CK (OEL STEL)	1468 mg/m³
Chemical category	Sensitizer
Ireland - Occupational Exposure Limits	
OEL TWA [1]	734 mg/m³
OEL TWA [2]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Italy - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³

Ethyl acetate (141-78-6)	
OEL STEL [ppm]	400 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	200 mg/m³
OEL TWA [ppm]	54 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	500 mg/m³
IPRV (OEL TWA) [ppm]	150 ppm
NRV (OEL C)	1100 mg/m³
NRV (OEL C) [ppm]	300 ppm
Luxembourg - Occupational Exposure Limits	
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Malta - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Netherlands - Occupational Exposure Limits	
MAC-TGG (OEL TWA)	734 mg/m³
MAC-15 (OEL STEL)	1468 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	734 mg/m³
NDSCh (OEL STEL)	1468 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	734 mg/m³ (indicative limit value)
OEL TWA [ppm]	200 ppm (indicative limit value)
OEL STEL	1468 mg/m³ (indicative limit value)
OEL STEL [ppm]	400 ppm (indicative limit value)
Romania - Occupational Exposure Limits	
OEL TWA	400 mg/m³
OEL TWA [ppm]	111 ppm
OEL STEL	500 mg/m³
OEL STEL [ppm]	139 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	734 mg/m³
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL C)	1100 mg/m³
Slovenia - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm

Ethyl acetate (141-78-6)	
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	734 mg/m³
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	1468 mg/m³
VLA-EC (OEL STEL) [ppm]	400 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	550 mg/m³
NGV (OEL TWA) [ppm]	150 ppm
KTV (OEL STEL)	1100 mg/m³
KTV (OEL STEL) [ppm]	300 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	734 mg/m³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	1468 mg/m³
WEL STEL (OEL STEL) [ppm]	400 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	734 mg/m³
Grenseverdi (OEL TWA) [2]	200 ppm
Korttidsverdi (OEL STEL)	1468 mg/m³ (value from the regulation)
Korttidsverdi (OEL STEL) [ppm]	400 ppm (value from the regulation)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	730 mg/m³
MAK (OEL TWA) [2]	200 ppm
KZGW (OEL STEL)	1460 mg/m³
KZGW (OEL STEL) [ppm]	400 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	400 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:
Avoid all unnecessary exposure.
Personal protective equipment symbol(s):

8.2.2.1. Eye and face protection

Eye protection:
Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:
Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.
Other information:
Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	light yellow. amber.
Odour	:	Fruity.
Odour threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	≥ 93.33 °C (closed cup) ASTM D7094
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Non flammable.
Vapour pressure	:	No data available
Relative vapour density at 20 °C	:	No data available
Relative density	:	≈ 1.08
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available

Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidising properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	:	Harmful if swallowed.
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Pomegranate Noir #TCDL-CFRA-BOWL-NPOM	
ATE CLP (oral)	733.84 mg/kg bodyweight

Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 18000 mg/kg
LC50 Inhalation - Rat [ppm]	4000 ppm/4h

Veltol plus crystals (4940-11-8)	
LD50 oral rat	1150 mg/kg
LD50 oral	1200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg

Methyl oct-2-ynoate (111-12-6)	
LD50 oral rat	1530 mg/kg

Citronellyl acetate (mixed Isomers) (150-84-5)	
LD50 oral rat	6800 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Verdox (88-41-5)	
LD50 oral rat	4600 mg/kg
LD50 oral	4600 mg/kg bodyweight

Vanillin (121-33-5)	
LD50 dermal rabbit	> 5010 mg/kg

Dimethylbenzyl carbinyl butyrate(DMBCB) (10094-34-5)	
LD50 oral rat	> 5 g/kg

Aldehyde C-16 (77-83-8)	
LD50 oral rat	5470 mg/kg
LD50 dermal rat	> 2000 mg/kg

Aldehyde C-14 (104-67-6)	
LD50 oral rat	18500 mg/kg
LD50 dermal rat	> 2000 mg/kg

Benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg
LD50 oral	1500 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg
LD50 dermal	4000 mg/kg bodyweight

Hexyl cinnamic aldehyde (101-86-0)	
LD50 oral rat	3100 mg/kg
LD50 oral	3100 mg/kg bodyweight
LD50 dermal rabbit	> 3000 mg/kg
LC50 Inhalation - Rat	> 5 mg/l/4h

Hexamethylindanopyran (1222-05-5)	
LD50 oral rat	> 3250 mg/kg
LD50 dermal rabbit	> 3250 mg/kg

Lime oil distilled (8008-26-2)	
LD50 oral rat	5600 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Skin corrosion/irritation	:	Not classified
Serious eye damage/irritation	:	Not classified
Respiratory or skin sensitisation	:	May cause an allergic skin reaction.
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
STOT-single exposure	:	Not classified

Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	:	Not classified
Aspiration hazard	:	Not classified
Potential adverse human health effects and symptoms	:	Based on available data, the classification criteria are not met,Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	:	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	:	Not classified
Hazardous to the aquatic environment, long-term (chronic)	:	Toxic to aquatic life with long lasting effects.

Ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Veltol plus crystals (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

Citronellyl acetate (mixed Isomers) (150-84-5)	
LC50 - Fish [1]	6.1 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])

Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])

Aldehyde C-16 (77-83-8)	
LC50 - Fish [1]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

Aldehyde C-14 (104-67-6)	
LC50 - Fish [1]	569 mg/l 96 h

EC50 - Crustacea [1]	5.85 mg/l 48 h
EC50 - Other aquatic organisms [1]	5.94 mg/l 72 h

Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC (chronic)	0.168 mg/l

Hexamethylindanopyran (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 µg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier

12.2. Persistence and degradability

Pomegranate Noir #TCDL-CFRA-BOWL-NPOM	
Persistence and degradability	Not established.

Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Pomegranate Noir #TCDL-CFRA-BOWL-NPOM	
Bioaccumulative potential	Not established.

Ethyl acetate (141-78-6)	
BCF - Fish [1]	30
Partition coefficient n-octanol/water (Log Pow)	0.6

Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)

Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	4
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1 UN number

UN-No. (ADR) : UN 3082

UN-No. (IMDG) : UN 3082

UN-No. (IATA) : UN 3082

UN-No. (ADN) : UN 3082

UN-No. (RID) : UN 3082

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.

Proper Shipping Name (ADN) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Proper Shipping Name (RID) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport document description (ADR) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXAMETHYLINDANOPYRAN), 9, III, (E)

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXAMETHYLINDANOPYRAN), 9, III, MARINE POLLUTANT

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (HEXAMETHYLINDANOPYRAN), 9, III

Transport document description (ADN) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III

Transport document description (RID) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 9

Danger labels (ADR) : 9

:

IMDG

Transport hazard class(es) (IMDG) : 9

Danger labels (IMDG) : 9

:

IATA

Transport hazard class(es) (IATA) : 9

Danger labels (IATA) : 9

: 

ADN

Transport hazard class(es) (ADN) : 9

Danger labels (ADN) : 9

: 

RID

Transport hazard class(es) (RID) : 9

Danger labels (RID) : 9

: 

14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : III

Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 601, 375

Limited quantities (ADR) : 5l

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions (ADR) : TP1, TP29

Tank code (ADR) : LGBV

Vehicle for tank carriage : AT

Transport category (ADR) : 3

Special provisions for carriage - Packages (ADR) : V12

Special provisions for carriage - Loading, unloading and handling (ADR) : CV13

Hazard identification number (Kemler No.) : 90

Orange plates : 

Tunnel restriction code (ADR) : E

EAC code : •3Z

Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197
ERG code (IATA)	: 9L

Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
Reference code	Applicable on

3(a)	Ethyl acetate
3(b)	**Pomegranate Noir** #TCDL-CFRA-BOWL-NPOM ; Ethyl acetate ; Methyl oct-2-ynoate ; Citronellyl acetate (mixed Isomers) ; Liffarome ; Hexyl cinnamic aldehyde ; Aldehyde C-16 ; Benzyl benzoate
3(c)	**Pomegranate Noir** #TCDL-CFRA-BOWL-NPOM ; Verdox ; Methyl oct-2-ynoate ; Citronellyl acetate (mixed Isomers) ; Dimethylbenzyl carbinyl butyrate(DMBCB) ; Hexyl cinnamic aldehyde ; Aldehyde C-14 ; Aldehyde C-16 ; Benzyl benzoate ; Hexamethylindanopyran
40.	Ethyl acetate

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Liffarome is listed

SZW-lijst van mutagene stoffen : Liffarome is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H224	Extremely flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.